

SN-2024 A ALUMINUM STRUCTURAL DOLLIES

PROFILE

- ◆ ALUMINUM STRUCTURAL DOLLY CONSTRUCTED FROM 3/16" DIAMETER X 1 1/2" X 1 1/2" ALUMINUM ANGLE, LIP-ANGLED-UP CONSTRUCTION.
- ◆ CUSTOM DESIGN OPTIONS
- ◆ ONE-PIECE FRAME CONSTRUCTION WITH CRUSH BENT CORNERS AND FULLY WELDED NOTCHED CROSSBARS.
- ◆ EACH DOLLY CONTAINS FOUR BOLTED-ON 5" X 2" HARD POLYPROPYLENE CASTERS - TWO SWIVEL AND TWO STATIONARY, DIRECTION OF FLOW LENGTHWISE. EACH CASTER IS RATED AT 800 LBS LOADING, AND FEATURES DELRIN BEARINGS, GREASE FITTINGS, AND BOLT TOGETHER CONSTRUCTION USING ZINC-PLATED FASTENERS.
- ◆ DOLLY LOAD RATING UP TO 1800 LBS.
- ◆ DOLLY SHIPPED FULLY ASSEMBLED
- ◆ OUTSIDE DIMENSION 24 3/8" X 20 3/8" X 8 1/4" (LWH INCHES).
- ◆ INSIDE DIMENSION (TOP) 24" X 20".
- ◆ WEIGHT - 13.6 POUNDS



MANUFACTURED BY:
WRH INDUSTRIES LTD.
957 AIRPORT ROAD
FALL RIVER, MA 02720 USA
WWW.WRH.NET

1-800.FDA.TRAY (332-8729)
+1-508-674-2444
FAX: +1-508-674-2666
EMAIL: INFO@WRH.NET
REV 08-07-02